

DECLARATION OF PERFORMANCE 210



1. Unique identification code of the product-type:

Wall and ceiling cladding made of solid wood with tongue and groove for interior use –
 Spruce, Fir, Pine, Douglas Fir, Larch

2. Intended use or uses:

I = interior use, WC = wall and ceiling elements

3. Manufacturer:

Rettenmeier Holzindustrie Wilburgstetten GmbH, Industriestraße 1, 91634 Wilburgstetten, Germany

4. System or systems for assessment and verification of constancy of performance (AVCP):

System 4

5. Designated standard / UK approved body or bodies:

Designated standard: EN 14915:2013+A2:2020

UK approved body or bodies: Not applicable (System 4)


6. Declared performance:

Manufacture of solid wood profiles and panels for wall and ceiling applications in accordance with EN 14519 and visual grading in accordance with EN 14519 for spruce, fir, pine, Douglas fir and larch. Untreated or treated with Osmo WM 029-289, WM 029-315, 7003 (see product data sheets). Thicknesses from 7 mm to 50 mm, widths from 70 mm to 210 mm.

| Essential characteristics | | Performance | | Designated standard |
|---------------------------|--|------------------------|--------------|---------------------|
| | | untreated | treated | |
| Reaction to fire | Minimum thickness 9/6 mm / without air gap | D-s2, d2 | NPD | EN 14915:2013 |
| | Minimum thickness 9/6 mm / with open air gap | D-s2, d0 | NPD | |
| | Minimum thickness 12/8 mm / without air gap | D-s2, d0 | NPD | |
| | Formaldehyde emission | E 1 | E 1 | |
| | Pentachlorophenol content | NPD | NPD | |
| | Water vapour permeability μ (density kg/m ³) | 50–110 (450–620) | NPD (NPD) | |
| | Release of dangerous substances | NPD | NPD | |
| | Sound absorption (250–500 Hz / 1000–2000 Hz) | 0,1 / 0,3 | 0,1 / 0,3 | |
| | Thermal conductivity W/(mK) (mean density kg/m ³) | 0,11–0,16 (420–620) | NPD (NPD) | |
| | Fastener withdrawal resistance | NPD | NPD | |
| Durability | Spruce (PCAB) | 4 acc. to EN 350-2 | NPD | |
| | Fir (ABAL) | 4 acc. to EN 350-2 | NPD | |
| | Pine (PNSY) | 3-4 acc. to EN 350-2 | NPD | |
| | Douglas fir (PSMN) | 3-4 acc. to EN 350-2 | NPD | |
| | Larch (LADC) | 3-4 acc. to EN 350-2 | NPD | |

The performance of the product identified above is in conformity with the declared performance(s). This declaration is issued, in accordance with the Construction Products Regulation as retained in UK law, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:




rettenmeier[®]
 PREMIUM OF WOOD
 Rettenmeier Holding AG
 Industriestraße 1
 91634 Wilburgstetten
 GERMANY



rettenmeier[®]
 PREMIUM OF WOOD
 Rettenmeier Holzindustrie
 Wilburgstetten GmbH
 Industriestraße 1
 91634 Wilburgstetten
 GERMANY

Dr. Stephan Lang, Director Rettenmeier Holding AG

Wilburgstetten, 20.05.2026