

CE SAWN TIMBER

Our CE products meet all requirements with regard to **load-bearing capacity** and **labelling**.



KVH®

QLH DUO/TRIO

BSH

CE SAWN TIMBER

SAWN TIMBER

LEARN
MORE ...





ROOF SLATS

CE/S10

PRODUCT DESCRIPTION:

- sawn timber spruce/fir
- certified according to DIN EN 14081
- graded according to DIN 4074 S10
- dried to approximately 18% ± 2% wood moisture content
- finely sawed
- lengths 50 : 50 cm, ascending

- ✓ cost-effective
- ✓ standard quality
- ✓ wide range of applications

Examples of applications: Slats for roofing, substructure timbers for exterior facades, wall and ceiling cladding, battens, counter slats, etc.

	Dimension (mm)	Quality	pcs/pallet	Lengths (m)	fresh raw	freshly pressure-treated	dry raw
CE slats, spruce/fir, S10, DIN 4074, unplanned, fresh or dry, made in Germany 							
	31 x 52	S10	280	4.00 - 5.00	x	x	
	41 x 62	S10	216	4.00 - 5.00	x	x	
	30 x 50	S10	280	4.00 - 5.00			x
	40 x 60	S10	216	4.00 - 5.00			x

Other lengths on request

CE ROOF FORMWORK

DRY

KVH®

QLH DUO/TRIO

BSH

CE SAWN TIMBER

SAWN TIMBER

PRODUCT DESCRIPTION:

- sawn timber, spruce/fir C24M TS DIN EN 14081
- machine grading according to strength
- dried to approximately 18% ± 2% wood moisture content
- finely sawed
- raw
- dry strength durable



- ✓ calculable as load-bearing component
- ✓ quality-tested

Application examples: Especially as roof lining for load-bearing purposes on the roof

	Dimension (mm)	Quality	pcs/pallet	Lengths (m)	fresh raw	dry pressure-treated	dry raw
CE roof formwork, spruce/fir, C24M TS, made in Germany 							
	24 x 160	C24M	273	4.00 - 5.00			x

T&G TIMBER MANUFACTURED FROM RAW MATERIAL C24M TS

✓ quality-tested

PRODUCT DESCRIPTION:

- manufactured from
sawn timber spruce/fir
C24M TS DIN EN 14081
- dried to approximately
18% ± 2% wood
moisture content
- finely sawed
- raw
- dry strength durable

Examples of applications: Attic, outbuildings, subfloors, garden house, substructure for wall and ceiling cladding, etc.

	Dimension (mm)	Quality	pcs/pallet	Lengths (m)	fresh raw	dry pressure- treated	dry raw
T&G timber with taper groove from raw materials C24M TS, spruce/fir, made in Germany 							
	24 x 136	made of C24M	160	4.00 - 5.00			x
							